

# Data Sheet

## FUJITSU Server PRIMERGY RX2520 M1 Dual socket 2U rack server

Scalable rack server for essential business apps

FUJITSU Server PRIMERGY systems provide the most powerful and flexible data center solutions for companies of all sizes, across all industries and for any type of workload. This includes expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as density-optimized scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, and provide more agility in daily operations in order to turn IT faster into a business advantage.

FUJITSU Server PRIMERGY RX rack systems are versatile rack-optimized servers providing best-in-class performance and energy efficiency, and thus form the "standard" in each data center. PRIMERGY RX servers deliver 20 years of development and production know-how resulting in extremely low failure rates below market average, and lead to continuous operations and outstanding hardware availability.

### PRIMERGY RX2520 M1

The Fujitsu PRIMERGY RX2520 M1 is an efficient and scalable platform for essential business applications. As a dual socket rack server it features the latest Intel® Xeon® processor E5-2400 v2 product family with up to 192 GB RAM. The PRIMERGY RX2520 delivers an especially well balanced price / performance ratio. Its compact PRIMERGY 2U modular chassis provides storage demanding applications and services a powerful environment of up to twelve 3.5-inch or sixteen 2.5-inch storage drives. Furthermore, the RX2520 is prepared for future demands by offering further modular options and upgrade kits for LAN, RAID and storage. Power supply units with 96 % efficiency and the enhanced iRMC S4 management will result in lower operational costs.



# Features & Benefits

Main Features	Benefits
<p><b>Well-balanced price / performance ratio</b></p> <ul style="list-style-type: none"> <li>■ Intel® Xeon® E5-2400 v2 product family with up to 10 cores</li> <li>■ Up to 192 GB RAM (12 DIMM slots) and up to 6 PCIe slots, 768 GB RAM on special release</li> </ul> <p><b>Flexible and scalable platform</b></p> <ul style="list-style-type: none"> <li>■ Huge number of storage drives of up to twelve 3.5-inch or sixteen 2.5-inch storage drives, prepared for 12Gits / SAS 3</li> <li>■ Modular concept for the base unit as well as a choice for LAN controller, RAID controller and power supplies</li> <li>■ Upgrade kits for hard disk drives and backup devices (3.5-inch and 5.25-inch)</li> </ul> <p><b>Cost efficient operations</b></p> <ul style="list-style-type: none"> <li>■ Simplified power management with different pre-defined power profiles</li> <li>■ 2 hot-plug PSU with 96% efficiency (80Plus titanium)</li> <li>■ Fujitsu ServerView Suite offers tools for installation and deployment, permanent status monitoring and control. A wide range of integration packs allow a seamless and easy integration in widely used enterprise management systems</li> </ul>	<ul style="list-style-type: none"> <li>■ Provides a well-balanced price / performance ratio for essential business applications or small virtualization environments</li> <li>■ Scalable platform to best meet future demand</li> <li>■ High storage capacity for storage demanding applications and scale-out scenarios</li> <li>■ Individual and cost-saving configuration of the server according to the need of today with upgrade options to meet the demand of tomorrow</li> <li>■ Upgrade kits save budget as the system can be upgraded when the company grows and thus protect the investment</li> <li>■ Simplified and comprehensive power management that results with the high efficient power supplies in significant savings</li> <li>■ Fujitsu ServerView Suite provides all the functions for fail-safe, flexible and automated 24x7 server operations and improves end-user productivity via intelligent and innovative system management solutions.</li> </ul>

# Technical details

## PRIMERGY RX2520 M1

Base unit	PRIMERGY RX2520 M1 LFF	PRIMERGY RX2520 M1 LFF	PRIMERGY RX2520 M1 SFF
Housing types	Rack	Rack	Rack
Storage drive architecture	max. 8x 3.5-inch SAS/SATA	max. 12x 3.5-inch SAS/SATA/SSD	max. 16x 2.5-inch SAS/SATA
Power supply	Hot-plug	Hot-plug	Hot-plug
Product Type	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server

## Mainboard

Mainboard type	D3169
Chipset	Intel® C600 (Patsburg A)
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5-2400 v2 product family

Processor	Intel® Xeon® processor E5-2403v2 (4C/4T, 1.80 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1,333 MHz, 80 W)
	Intel® Xeon® processor E5-2407v2 (4C/4T, 2.40 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1,333 MHz, 80 W)
	Intel® Xeon® processor E5-2420v2 (6C/12T, 2.20 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 80 W)
	Intel® Xeon® processor E5-2430Lv2 (6C/12T, 2.40 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 60 W)
	Intel® Xeon® processor E5-2430v2 (6C/12T, 2.50 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 80 W)
	Intel® Xeon® processor E5-2440v2 (8 Cores / 16 Threads, 1.90 GHz, TLC: 20 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 95 W)
	Intel® Xeon® processor E5-2450Lv2 (10C/20T, 1.70 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 60 W)
	Intel® Xeon® processor E5-2450v2 (8C/16T, 2.50 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 95 W)
Intel® Xeon® processor E5-2470v2 (10C/20T, 2.40 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 95 W)	

Memory slots	12 (6 DIMMs per CPU, 3 channels with 2 slots per channel)
Memory slot type	DIMM (DDR3)
Memory capacity (min. - max.)	2 GB - 192 GB
Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™)
Memory notes	Supports DDR3 800 / 1066 / 1333 / 1600 RDIMM max. 6 memory modules/CPU with single or dual-rank RDIMM or single, dual-rank or quad-rank Load-Reduced (LR) DIMM. Performance Mode with identical modules in all three channels (2 modules per bank). Support of 32GB and 64GB LR-DIMMs on project release only.

Memory options	4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, single rank
	8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, single rank
	16 GB (1 module(s) 16 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank

## Interfaces

USB 2.0 ports	9 x USB 2.0 (2x front for 2.5" and 1x front for 3.5" chassis, 4x rear, 2x internal for backup devices, 1x UFM)
Graphics (15-pin)	2 x VGA (thereof 1x front optional)
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC or system or shared
LAN / Ethernet	2 x Gbit/s Ethernet (RJ45) with upgrade options for additional 2x1 Gbit/s (RJ45), 4x 1 Gbit/s (RJ45) or 2x 10 Gbit/s (SFP+)
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard Gbit LAN port

## Onboard or integrated Controller

RAID controller	4 port for internal 3 Gbit/s SATA and 3 Gbit/s SAS (as upgrade option with SAS enabling key) for HDDs with RAID 0/1/10 (Intel C600) additional RAID controller options are described under Components RAID controller
SATA Controller	Intel® C600, 1 x SATA channel for ODD
LAN Controller	Intel® Ethernet Controller I210. 2 x 1Gbit/s Ethernet Controller (10/100/1000 Mbit/s). PXE-Boot via LAN from PXE server, iSCSI boot (also diskless)
Remote management controller	IPMI 2.0 compatible Integrated Remote Management Controller (iRMC S4, 256 MB attached memory incl. graphics controller)

**Onboard or integrated Controller**

Trusted Platform Module (TPM)	Infineon / separate module; TCG V1.2 compliant (option)
-------------------------------	---

**Slots**

PCI-Express 3.0 x8	6 x Low profile
--------------------	-----------------

PCI-Express 2.0 x4 (mech. x8)	1 x Low profile
-------------------------------	-----------------

Slot Notes	Important: The number of PCIe slots depends on the number of CPUs: 5x PCIe x8 Gen 3 (2x CPU1; 3x CPU2; mechanical x8) 1x PCIe x4 Gen 2 (PCH; mechanical x8) Internal Slots: 1x PCIe x8 Gen 3 (CPU1; mechanical x8)
------------	--

**Drive bays**

Storage drive bays	2.5-inch base unit (max. 16 x 2.5) or 3.5-inch base unit (max. 12 x 3.5)
--------------------	--

Accessible drive bays	1 x 5.25/0.5-inch for ODD 1 x 5.25/0.5-inch for Local Service Display 1 x 3.5/1.6-inch for backup devices 1 x 5.25/1.6-inch for backup devices
-----------------------	---

Notes accessible drives	All possible options described in relevant system configurator.
-------------------------	---

**Drive bays (Base unit specific)**

Storage drive bays	Max 8 x 3.5-inch	Max 12 x 3.5-inch	Max 16 x 2.5-inch
Optional accessible drives	1 x ODD	-	up to 1 x ODD and/or backup device

**General system information**

Number of fans	2
----------------	---

Fan configuration	hot-plug / optional redundant
-------------------	-------------------------------

Fan notes	2 + 1 redundant option, additional fan for 2nd CPU
-----------	--

**Operating panel**

Operating buttons	On/off switch Reset button NMI button ID button
-------------------	--

Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
-------------	--

Service display	Optional: ServerView Local Service Display (LSD)
-----------------	---

**BIOS**

BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support
---------------	--

## Operating Systems and Virtualization Software

<b>Certified or supported operating systems and virtualization software</b>	Microsoft® Hyper-V Server 2012 R2
	Microsoft® Windows Server® 2012 R2 Datacenter
	Microsoft® Windows Server® 2012 R2 Standard
	Microsoft® Windows Server® 2012 R2 Essentials
	Microsoft® Windows Storage Server 2012 R2 Standard
	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Server® 2012 Essentials
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows® Server 2008 Datacenter
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	Microsoft® Windows® Web Server 2008
	VMware vSphere™ 6.0
	VMware vSphere™ 5.5
	VMware vSphere™ 5.1 Embedded
	VMware vSphere™ 5.1
	SUSE® Linux Enterprise Server 12
	SUSE® Linux Enterprise Server 11
	Red Hat® Enterprise Linux 7
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
	Red Hat® Enterprise Linux 5 with XEN
Citrix® XenServer®	
Oracle® Linux 7	
Oracle® Linux 6	
Oracle® VM 3	
<b>Operating system release link</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473</a>
<b>Operating system notes</b>	Support of other Linux derivatives on demand

## Server Management

<b>Standard</b>	<ul style="list-style-type: none"> <li>ServerView Suite - Deploy <ul style="list-style-type: none"> <li>SV Installation Manager</li> <li>SV Scripting Toolkit</li> </ul> </li> <li>ServerView Suite - Control <ul style="list-style-type: none"> <li>Operations Manager incl. PDA and ASR &amp; R (Prefailure and Analysis; Automatic Server Recovery and Restart)</li> <li>Agents and CIM Providers</li> <li>System Monitor</li> <li>RAID Manager</li> <li>Capacity Management</li> <li>Power Management</li> <li>Storage Support</li> </ul> </li> <li>ServerView Suite - Maintain <ul style="list-style-type: none"> <li>Remote Management (iRMC in combination with Intel® Node Manager)</li> <li>Update Management (BIOS, Firmware, Windows Drives and SV Agents)</li> <li>Performance Measurement</li> <li>Asset Management</li> <li>Online Diagnostics</li> </ul> </li> <li>ServerView Suite - Integrate <ul style="list-style-type: none"> <li>Integration packs e.g. for Microsoft System Center, VMware vCenter, Nagios, HP SIM and others</li> </ul> </li> <li>Deployment Solutions and others</li> </ul>
-----------------	---

**Server Management**

<b>Option</b>	ServerView Suite - Maintain iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media ServerView Suite - Dynamize Virtual-IO Manager (VIOM) Resource Orchestrator Virtual Edition (ROR VE) Resource Orchestrator Cloud Edition (ROR CE) ServerView Suite - Integrate Integration pack for Fujitsu ManageNow® solution
<b>Server Management notes</b>	Regarding dependencies for ServerView Suite software products see dedicated product data sheets.

**Dimensions / Weight**

<b>Rack (W x D x H)</b>	482.6 mm (Bezel) / 445mm (Body) x 770 x 86.9 mm
<b>Mounting Depth Rack</b>	735 mm
<b>Height Unit Rack</b>	2 U
<b>19" rackmount</b>	Yes
<b>Weight</b>	up to 25 kg
<b>Weight notes</b>	Actual weight may vary depending on configuration
<b>Rack integration kit</b>	Rack integration kit as option

**Environment**

<b>Operating ambient temperature</b>	5 - 40 °C (41 - 104 °F)
<b>Operating temperature note</b>	Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. For detailed information see relevant system configurator.
<b>Operating relative humidity</b>	10 - 85 % (non condensing)
<b>Operating environment</b>	FTS 04230 – Guideline for Data Center (installation specification)
<b>Operating environment link</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe">http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe</a>
<b>Noise emission</b>	Measured according to ISO 7779 and declared according to ISO 9296
<b>Sound pressure (LpAm)</b>	Minimum noise : 34 dB(A) (idle) / 34 dB(A) (operating) Typical noise : 36 dB(A) (idle) / 36 dB(A) (operating)
<b>Sound power (LWAd; 1B = 10dB)</b>	Minimum noise : 5.76 B (idle) / 5.76 B (operating) Typical noise : 6.1 B (idle) / 6.1 B (operating)
<b>Noise notes</b>	Noise emissions depends on operation modes, system configuration and ambient temperature.

**Electrical values**

<b>Power supply configuration</b>	1x hot-plug power supply or 2x hot-plug power supply for redundancy
<b>Hot-plug power supply redundancy</b>	Optional
<b>Active power (max. configuration)</b>	643 W
<b>Apparent power (max. configuration)</b>	600 VA
<b>Rated current max.</b>	5.5 A (100 V) / 2.5 A (240 V)
<b>Heat emission</b>	2314.8 kJ/h (2194.0 BTU/h)
<b>Power supply</b>	450W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz

**Compliance**

<b>Global</b>	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)
<b>Germany</b>	GS
<b>Europe</b>	CE
<b>USA/Canada</b>	CSAc/us FCC Class A
<b>Japan</b>	VCCI:V3 Class A + JIS 61000-3-2
<b>China</b>	CCC (depending on configuration)
<b>Australia/New Zealand</b>	C-Tick
<b>Compliance link</b>	<a href="http://globalsp.ts.fujitsu.com/sites/certificates">http://globalsp.ts.fujitsu.com/sites/certificates</a>

---

## Compliance

### Compliance notes

There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.

\* Warning:

This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

# Components

---

### Backup Drives

LTO3HH Ultrium, 400 GB, 60 MB/s, half height, SAS 3Gb/s

LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 6Gb/s

LTO5HH Ultrium, 1,500 GB, 140 MB/s, half height, SAS 6Gb/s

LTO6HH Ultrium, 2,500 GB, 160 MB/s, half height, SAS 6Gb/s

RDX Drive, 320 GB, 500 GB, 1 TB, 25 MB/s, half height, USB 3.0

---

### Optical drives

Blu-ray Disc™ Triple Writer, (6x BD-ROM; 8x DVD; 24x CD), slimline, SATA I

DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I

## Hard disk drives

HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 250 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 3 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 900 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 450 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 146 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 3 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical



<b>Solid-State-Drive</b>	SSD SATA, 6 Gb/s, 800 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 800 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
	SSD SATA, 6 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 480 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 480 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
	SSD SATA, 6 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 240 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
	SSD SATA, 6 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 120 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 120 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 100 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
	SSD SATA, 6 Gb/s, 100 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
DOM SATA, 6 Gb/s, 128 GB, non hot plug, enterprise, 345TBW (Seq. write)	
DOM SATA, 6 Gb/s, 64 GB, non hot plug, enterprise, 172TBW (Seq. write)	
DOM SATA, 6 Gb/s, 32 GB, non hot plug, enterprise, 86TBW (Seq. write)	
<b>SCSI / SAS Controller</b>	SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
	SAS Ctrl. 12 Gbit/s 8 ports ext. PCIe 3.0 x8
	SAS Ctrl. 6 Gbit/s 8 ports ext. PCIe 2.0 x8
<b>RAID Controller</b>	RAID Ctrl., SAS/SATA 12 Gbit/s, Fujitsu PRAID CP400i, 8 ports int. RAID level: 0, 1, 1E, 10, 5, 50 No BBU support
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, LSI LSI MegaRAID SAS 9286CV-8e, RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116C), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
	RAID 0/1 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 0/1 (D2607), 8 ports int. RAID level: 0, 1, 10, No BBU support
<b>Fibre Channel controller</b>	Fibre Channel Host Bus Adapter 1 x 8 Gbit/s Qlogic QLE2560 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gbit/s Qlogic QLE2562 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 8 Gbit/s Emulex LPe1250 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gbit/s Emulex LPe12002 MMF LC-style
<b>Communication, Network</b>	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.0 x8 SFP+ ( Fujitsu )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.1 x8 RJ45 ( Intel® )
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
<b>Rack infrastructure</b>	Rackmount kit full extraction (820mm), tool less mounting, length variable 559-914mm
	Cable Management for 19-inch DataCenter / PRIMECENTER Racks
	Cable Arm 2U for PRIMECENTER- and 3rd-party racks
<b>Warranty</b>	
<b>Warranty period</b>	3 years

---

**Warranty**

**Warranty type** Onsite warranty

**Warranty Terms & Conditions** [www.fujitsu.com/support](http://www.fujitsu.com/support)

**Product Support Services - the perfect extension**

**Support Pack Options** Globally available in major business areas:  
9x5, Next Business Day Onsite Response Time  
9x5, 4h Onsite Response Time  
24x7, 4h Onsite Response Time

**Recommended Service** 24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.

**Service Lifecycle** 5 years after end of product life

**Service Weblink** <http://www.fujitsu.com/fts/products/product-support-services/>

# More information

## Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY RX2520 M1, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu PRIMERGY RX2520 M1, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://www.fujitsu.com/primergy>

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
©2015 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

FUJITSU LIMITED

Website: [www.fujitsu.com](http://www.fujitsu.com)  
2015-10-07 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
© 2015 Fujitsu Technology Solutions GmbH



[www.forefrontec.com](http://www.forefrontec.com)  
[info@forefrontec.com](mailto:info@forefrontec.com)

Jebel Ali Free Zone, Dubai(HO)  
Street No. N503 - FD03, FD04 & FD05  
United Arab Emirates  
P.O. Box 17020

Tel: +971 (4) 881 44 40  
Fax: +971 (4) 881 42 42

Al Olaya Street, Riyadh(BO)  
Akariyah-3 Building, Office 610  
Kingdom of Saudi Arabia  
P.O. Box 301807, Riyadh 11372

Tel: +966 (11) 460 35 80  
Fax: +966 (11) 460 35 85

Qasim Zainah Street, Jeddah(BO)  
Al-Rawdah, Al-Rawdah Plaza,  
Office 204  
Kingdom of Saudi Arabia

Tel: +966 (12) 612 14 63  
Fax: +966 (12) 612 05 17

Forefront Technologies(BO)  
Musheireb - Palestine St.,  
Doha - Qatar

Tel: +974 (3) 394 47 59  
Fax: +971 (4) 881 42 42

Forefront Technologies(BO)  
Khuwair,  
Muscat, Oman

Tel: +968 (9) 774 24 70  
Fax: +971 (4) 881 42 42