

Data Sheet

FUJITSU Server PRIMERGY BX900 S2 Blade System

Elasticity for dynamic adaption to changing requirements

FUJITSU Server PRIMERGY systems provide the most powerful and flexible data center solutions for companies of all sizes, across all industries and for any type of workload. This includes expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as density-optimized scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, and provide more agility in daily operations in order to turn IT faster into a business advantage.

Fujitsu Server PRIMERGY BX blade systems are the perfect platform to build a converged infrastructure designed to reduce IT costs, time and efforts. PRIMERGY Blade Servers utilizes a modular architecture and contain in addition to the compute power, all required infrastructure and network components, storage capacity as well as management modules that helps companies to simplify their infrastructure, achieve significant cost reductions and increase flexibility.

PRIMERGY BX900 S2

The Fujitsu Server PRIMERGY BX900 S2 is the accelerated dynamic server infrastructure in a single cube. This blade server can be dynamically adapted to various IT requirements and provides significant economic advantages for a large and growing number of applications. The PRIMERGY BX900 S2 has space for up to 18 server and storage blades in a 10U chassis. Thus it's the leader in its class for density in a compact form factor. Fujitsu's Cool-safe™ cooling concept, combined with power supply units certified with 80Plus Platinum and holistic power management, reduce your costs and ensures a more efficient use of energy and cooling capacity. Centralized management of physical and

virtualized environments and comprehensive I/O virtualization capabilities, combined with a fully redundant system design, supports business agility. Furthermore the PRIMERGY BX900 S2 provides future-proof connectivity enhancements with support of high speed InfiniBand (FDR InfiniBand) with 56 Gbit/s bandwidth. Server blades, equipped with CPUs from the next generation Intel® Xeon® processor E5-2400v2 / E5-2600v3 product family, offers scalable performance to meet highest requirements of extensive virtualization/consolidation scenarios for business critical applications on the one hand, and demanding high performance computing applications on the other hand. Packed with advanced features, up to 24 high-speed DIMM slots and flexible 10Gbit/s Universal Converged Network Adapter (UCNA) on board, the new PRIMERGY server blades provides the highest memory modules density in a dual-socket blade and allows doing more with a two-processor server than ever before.



Features & Benefits

Main Features	Benefits
<p>Dynamic Power & Cooling</p> <ul style="list-style-type: none"> Using our Cool-safe™ cooling concept, combined with 94% efficient power supplies and the enhanced ServerView power management software, it ensures maximum dynamic power & cooling. Combined with the 94% PSUs, the holistic power management enables for most accurate control of predefined maximum chassis power consumption. 	<ul style="list-style-type: none"> Save energy costs as never before - guaranteed
<p>Dynamic Virtualization</p> <ul style="list-style-type: none"> Equipped with server blades that are utilizing CPUs out of the latest generation Intel® Xeon® processor E5-2400v2 / E5-2600v3 product family, very large memory capacities and extended I/O performance, the PRIMERGY BX900 S2 is once again the optimal system for any virtualization scenario on the one hand, and for resource and performance hungry applications on the other hand. 	<ul style="list-style-type: none"> Easily deploy more or larger virtual and physical machines than ever before and in this way increase your IT performance and consolidation ratio.
<p>Dynamic High Availability</p> <ul style="list-style-type: none"> Due to its fully redundant design (management blades, connection blades, fans, PSUs), and in combination with ServerView Resource Orchestrator (ROR), the PRIMERGY BX900 S2 can completely protect itself against any possible failure; at the same time it excels with the fastest automatic recovery, and with a flexible allocation of its available resources to services, according to requirements. 	<ul style="list-style-type: none"> Best availability, most effective server protection and the agility to adapt to changing requirements.
<p>Dynamic Scalability</p> <ul style="list-style-type: none"> With space for up to 18 server and/or storage Blades, 8 connection blades, 6 power supply units and 2 management blades in a 10U high chassis, the PRIMERGY BX900 S2 incorporates the highest density. Combined with switch blade stacking the system allows highly flexible scaling and simplified management. 	<ul style="list-style-type: none"> Complete investment protection and flexible growth scenarios.
<p>New Performance level</p> <ul style="list-style-type: none"> PRIMERGY BX900 S2 supports high speed Infiniband (FDR Infiniband) with 56 Gbit/s bandwidth per port at a new level of payload efficiency; the encoding algorithm of 64b/66b instead of 8b/10b with QDR Infiniband results in a more than 70% enhanced ratio of net to gross data rate. 	<ul style="list-style-type: none"> Get the most out of your investment by operating at highest efficiency

Technical details

PRIMERGY BX900 S2

Base unit	PRIMERGY BX900 S2
Housing types	Rack

Enclosure

System unit type	10 U chassis for 19-inch rack
Front bays	18 half height or 9 full height bays for server or storage blades
Midplane	High speed midplane with 4 redundant fabrics
Rear bays	8 x for Connection Blades (2 Connection Blades per fabric) 6 x for PSU modules
Management Blades	1x hot-plug Management Blade as standard, redundant Management Blade as option
Fan configuration	Up to 3 additional hot plug, redundant fan modules
Fan notes	2 fan units per module, 2 x 2 fans per unit; modules either part of PSU modules or independent components
Power supply configuration	Up to 6x hot-plug power supply module, 3x as minimum (4th to 6th power supply module necessary for redundancy, and depending on system configuration)

Operating panel

Operating buttons	On/off switch ID button
Status LEDs	Power (amber / green) System status (orange) Identification (blue)
Service display	ServerView Local Service Display for Blade (LSB)

Management Blade

Type of Unit	BX900 MMB S1
LAN / Ethernet (RJ-45)	2 x 1Gbit/s Ethernet
Management LAN (RJ45)	Dedicated Service LAN port for MMB (1Gb Ethernet)
Serial 1 (9-pin)	1 x RS-232-C
USB 2.0 ports	2 x (at rear side of the system)

Dimensions / Weight

Dimensions (W x D x H)	482.6 mm (Bezel) / 445mm (Body) x 778 x 438
Height Unit Rack	10 U
19" rackmount	Yes
Weight	Up to 191 kg
Weight notes	Fully assembled Actual weight may vary depending on configuration
Rack integration kit	Included

Electrical values

Max. input of single power supply	3200 W / 1600 W (240 V / 100 V)
Max. output of single power supply	2880 W / 1360 W (240 V / 100 V)
Rated voltage range	100 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	65A / 29A (100 V / 240 V)
Active power (max. configuration)	11,200 W
Heat emission	40320.0 kJ/h (38216.0 BTU/h)
Electrical value notes	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: http://configurator.ts.fujitsu.com/public/ Suitable power supply cables have to be ordered separately.

Environment

Operating ambient temperature	5 - 35 °C
-------------------------------	-----------

Environment

Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	< 79 dB(A) (operating) < 64 dB(A) (standby)
Sound power (LWAd; 1B = 10dB)	< 8,6 B

Compliance

Global	CB RoHS WEEE
Germany	GS
Europe	CE Class A *
USA/Canada	CSAc/us ULc/us FCC Class A
Japan	VCCI:V3 Class A + JIS 61000-3-2
Australia/New Zealand	C-Tick
Taiwan	BSMI
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Server and Storage Blades pluggable into system unit front side

Product Model name	Processor type support	Processor quantity support	Max. number per BX900	Memory slots total	Supported capacity RAM (max.)
PRIMERGY BX2560 M1	Intel® Xeon® processor E5-2600 v3 product family-based platform http://docs.ts.fujitsu.com/dl.aspx?id=e8217dbe-2999-4ecf-829a-4f3ac2fd3a19	1 - 2	18	16	1,024 GB
PRIMERGY BX2580 M1	Intel® Xeon® processor E5-2600 v3 product family-based platform http://docs.ts.fujitsu.com/dl.aspx?id=48c3c546-5c2f-4f60-bdd9-bf40448cefa4	1 - 2	18	24	1,536 GB
PRIMERGY BX920 S4	Intel® Xeon® processor E5-2400 v2 product family http://docs.ts.fujitsu.com/dl.aspx?id=33efe617-f9a6-44cf-ac8a-ab5eadfe03f0	1 - 2	18	12	768 GB
PRIMERGY SX960 S1			2		http://docs.ts.fujitsu.com/dl.aspx?id=489d2a0c-81f1-4d3e-aaa3-df55ac446930
PRIMERGY SX980 S2			max. 6, (for the US market max. 3x SX980 S2 can be installed) http://docs.ts.fujitsu.com/dl.aspx?id=5bbd7637-71eb-49ed-b5c9-b3e7737b42d5		

Connection Blades (CB) pluggable into system unit rear side

Connection type	Down-link ports	Up-link ports	Max. number per BX unit
Eth FEX 10Gb 16/8	16 x 10 Gbit/s Eth	8 x 10 Gbit/s (SFP+)	6 (CB Slot 1/2 3/4 5/6)
Eth Pass Thru 10Gb 18/18	18 x 1/10 Gbit/s Eth	18 x 1/10 Gbit/s (SFP/SFP+)	6 (CB Slot 1/2 3/4 5/6)
Eth Switch/IBP/EHM 10/40Gb 18/8 + 2	18 x 1/10 Gbit/s Eth	8 x 10 Gbit/s (SFP+), 2 x 40Gbit/s (QSFP+)	6 (CB Slot 1/2 3/4 5/6)

Connection Blades (CB) pluggable into system unit rear side

Connection type	Down-link ports	Up-link ports	Max. number per BX unit
Eth Switch/IBP/EHM 1Gb 18/6	18 x 1 Gbit/s Eth	6 x 1 Gbit/s (RJ45)	8 (CB Slot 1/2 3/4 5/6 7/8)
Eth Switch/IBP/EHM 1Gb 36/12	36 x 1 Gbit/s Eth	8 x 1 Gbit/s (RJ45), 4 x 1 Gbit/s (SFP)	8 (CB Slot 1/2 3/4 5/6 7/8)
Eth Switch/IBP/EHM 1Gb 36/8+2	36 x 1 Gbit/s Eth	8 x 1 Gbit/s (RJ45) , 2 x 10 Gbit/s (SFP+)	8 (CB Slot 1/2 3/4 5/6 7/8)
FC Pass Thru 8Gb 18/18	18 x 8 Gbit/s FC	18 x 8 Gbit/s (SFP/SFP+)	4 (CB Slot 3/4 5/6)
FC Switch 16Gb Brocade 14 Port	18 x 8/16 Gbit/s FC	8 x 8/16 Gbit/s (SFP+)	4 (CB Slot 3/4 5/6)
FC Switch 16Gb Brocade 26 Port	18 x 8/16 Gbit/s FC	8 x 8/16 Gbit/s (SFP+)	4 (CB Slot 3/4 5/6)
FC Switch 16Gb Brocade 26 Port Enterprise	18 x 8/16 Gbit/s FC	8 x 8/16 Gbit/s (SFP+)	4 (CB Slot 3/4 5/6)
FC Switch 8Gb Brocade 14 Port	18 x 8 Gbit/s FC	8 x 4/8 Gbit/s (SFP/SFP+)	4 (CB Slot 3/4 5/6)
FC Switch 8Gb Brocade 26 Port	18 x 8 Gbit/s FC	8 x 4/8 Gbit/s (SFP/SFP+)	4 (CB Slot 3/4 5/6)
FC Switch 8Gb Brocade 26 Port Enterprise	18 x 8 Gbit/s FC	8 x 4/8 Gbit/s (SFP/SFP+)	4 (CB Slot 3/4 5/6)
IB Switch 56Gb 18/18	18 x 56 Gbit/s IB	18 x 56 Gbit/s (QSFP)	3 (CB Slot 3/4 5/6 7/8)
SAS Switch 6Gb 18/6	18 x 6 Gbit/s SAS	6 x 6 Gbit/s SAS	2 (CB Slots 5+6)

Warranty

Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	www.fujitsu.com/support

Product Support Services - the perfect extension

Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time
Recommended Service	24x7 Onsite Service with 4h Onsite Response Time
Spare Parts availability	5 years
Service Lifecycle	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/products/product-support-services/

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY BX900 S2, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY BX900 S2, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
©2015 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU LIMITED

Website: www.fujitsu.com
2015-10-07 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2015 Fujitsu Technology Solutions GmbH



www.forefrontec.com
info@forefrontec.com

Jebel Ali Free Zone, Dubai(HO)
Street No. N503 - FD03, FD04 & FD05
United Arab Emirates
P.O. Box 17020

Tel: +971 (4) 881 44 40
Fax: +971 (4) 881 42 42

Al Olaya Street, Riyadh(BO)
Akariyah-3 Building, Office 610
Kingdom of Saudi Arabia
P.O. Box 301807, Riyadh 11372

Tel: +966 (11) 460 35 80
Fax: +966 (11) 460 35 85

Qasim Zainah Street, Jeddah(BO)
Al-Rawdah, Al-Rawdah Plaza,
Office 204
Kingdom of Saudi Arabia

Tel: +966 (12) 612 14 63
Fax: +966 (12) 612 05 17

Forefront Technologies(BO)
Musheireb - Palestine St.,
Doha - Qatar

Tel: +974 (3) 394 47 59
Fax: +971 (4) 881 42 42

Forefront Technologies(BO)
Khuwair,
Muscat, Oman

Tel: +968 (9) 774 24 70
Fax: +971 (4) 881 42 42