

Data Sheet

FUJITSU Storage ETERNUS DX600 S3 Disk System

Leading storage performance, automated quality of service



ETERNUS DX - Business-centric Storage

Combining leading performance architecture with automated quality of service management the Fujitsu Storage ETERNUS DX series aligns storage resources with business priorities, thus enabling higher system utilization and delivering increased system consolidation capabilities and a faster ROI. Unified scalable entry-level and midrange systems, a seamless family concept enabling system upgrades and ETERNUS SF, the unified management suite across the product line, reduce operational and migration costs. ETERNUS SF provides enterprise-class functionalities in the entry and midrange class and allows flexible disaster recovery and business continuity concepts for the different model sizes, thus decreasing investment costs

ETERNUS DX600 S3

The scalable, unified Fujitsu Storage ETERNUS DX600 S3 system delivers leading storage performance and automated quality of service management enabling a maximum of system utilization and contributing to a fast ROI. It is the perfect solution when consolidating data in large-scale databases, business-critical applications and business analytics / big data - all into one system. It provides ample headroom for demanding server / desktop virtualization environments and enterprise file services. Extensive high-availability and disaster recovery capabilities make ETERNUS DX600 S3 an ideal storage system for business-critical data.



Features & Benefits

| Main Features | Benefits |
|---|---|
| Market-leading performance combined with automated performance management | <ul style="list-style-type: none">■ Leading performance enables large-scale storage consolidation delivering a fast ROI■ Automatically aligns storage performance with business priorities■ Delivers reliable and predictable quality of service for business-critical data■ Enables the operation of productive and analytical tasks in parallel on one storage system■ High scalability within the system and upgrade options to higher system-class and bigger systems support high data increases at low costs of growth and ensure investment protection |
| Rock-solid operation | <ul style="list-style-type: none">■ Comprehensive high-availability, quality of service and disaster resilience functions ensure predictable and reliable operation■ Flexible disaster recovery, including transparent failover, with a multitude of snapshot concepts and remote replication between different models and generations■ Extensive non-disruptive maintenance and upgrade capabilities reduce planned downtimes |
| Truly unified architecture | <ul style="list-style-type: none">■ Unified SAN and NAS access drive system utilization improving ROI■ Unified management functions across the entire product line result in operational efficiency■ Unified connectivity supports a large range and many combinations of networking types■ Unified architecture allows flexible combinations of 2.5" and 3.5" disk types |

Technical details

General system information

| ETERNUS DX600 S3 | |
|---|--|
| No. of controllers | 2 |
| No. of host interfaces | 4-16 ports [iSCSI, FCoE, Ethernet(10Gbit/s)], 4-32 ports [FC], 8-32 ports [Ethernet(1Gbit/s)] |
| Maximum Cache Capacity | 128 GB (block) / 128 GB + 64 GB (block + file) |
| Extreme Cache | 5,600 GB |
| Extreme Cache Pool | 3,200 GB |
| Maximum Disk Drives | 1,056 |
| Max. no. of drive enclosures | 44 |
| Note | 44 with 2.5" or 3.5" DE, 16 with HD-DE or mixture of DEs up to Max no. Drives |
| Supported RAID levels | 0, 1, 1+0, 5, 5+0, 6 |
| Host Interfaces | Fibre Channel (16 Gbit/s, 8 Gbit/s, 4 Gbit/s) FCoE (10 Gbit/s) iSCSI (10 Gbit/s, 1 Gbit/s) Ethernet (10 Gbit/s, 1 Gbit/s) |
| Mixed host interfaces | Yes |
| Max. no. of hosts | 1,024 |
| Supported NAS protocols | CIFS (SMB 2.0), CIFS (SMB 3.0), NFSv2, NFSv3 |
| Maximum Storage Capacity | 8,448 TB |
| Drive Type | 2.5-inch, SAS, 15,000 rpm (600 GB / 300 GB) 2.5-inch, SAS, 10,000 rpm (1.8 TB / 1.2 TB / 900 GB / 600 GB / 300 GB) 2.5-inch, SAS (self-encrypting), 10,000 rpm (1.2 TB / 900 GB) 2.5-inch, Nearline SAS, 7,200 rpm (2 TB / 1 TB) 2.5-inch, SSD (1.92 TB / 960 GB / 1.6 TB / 800 GB / 400 GB) 2.5-inch, SSD (self-encrypting) (1.6 TB / 800 GB) 3.5-inch, Nearline SAS, 7,200 rpm (8 TB / 6 TB / 4 TB / 2TB) 3.5-inch, Nearline SAS (self-encrypting), 7,200 rpm (4 TB) 3.5-inch, SSD (1.92 TB / 960 GB / 1.6 TB / 800 GB / 400 GB) 3.5-inch, SSD (self-encrypting) (1.6 TB / 800 GB) HDDE, SAS, 10,000 rpm (1.2 TB) HDDE, Nearline SAS, 7,200 rpm (8 TB / 6 TB / 4 TB / 2 TB) HDDE, SSD (1.92 TB / 1.6 TB) |
| Note | 2.5-inch drives are available only for 2.5-inch drive enclosures and 3.5-inch drives are available only for 3.5-inch drive enclosures. 6 TB/ 8 TB Nearline SAS and 1.8 TB SAS drives are Advanced Format drives. |
| Max. no. of SSDs | unlimited |
| Mixed 2.5 inch/ 3.5 inch drive enclosures | Yes |
| Drive interface | Serial Attached SCSI (12 Gbit/s) |
| Back-end disk connectivity | 4 pairs of four-lane x 12 Gbit/s Serial Attached SCSI buses (SAS 3.0 wide) |
| Max. no. of LUNs | 16,384 |
| Max. LUN capacity | 128 TB |
| No. of snapshots - max. | 8,192 |
| Max. no. of copy generations | 512 |
| Eco-mode | Yes |
| Performance management | |
| Automated Storage Tiering | Yes |
| Quality of Service | Yes |
| Automated QoS | Yes |
| Wide striping | Yes |
| Note | Automation options can be activated via ETERNUS SF Software |

Continuity management

| | |
|---------------------------|--|
| Storage Cluster | Yes |
| Remote Copy functionality | Synchronous and asynchronous |
| Note | Options can be activated via ETERNUS SF Software |

Information security management

| | |
|----------------------|--|
| Data confidentiality | Self-Encrypting Disk, Controller based Encryption, HTTPS (SSL), One Time Password, RADIUS, SSH |
| Data integrity | Cache Protection, Data Block Guard, Disk Drive Patrol |

Availability management

| | |
|---------------------------------|---------------------------------------|
| Fast Recovery | Yes |
| Non-disruptive maintenance | Dedicated Hot Spare, Global Hot Spare |
| Non-disruptive firmware upgrade | Yes |
| Redundancy | RAID Controller, Fan, Power supply |
| Hot part replacement | Yes |

Capacity management

| | |
|---------------------------------------|-----|
| Thin Provisioning | Yes |
| RAID migration | Yes |
| LUN online expansion w/o interruption | Yes |
| Reporting function | Yes |
| Hot part expansion | Yes |

Management

| | |
|---------------------|--|
| Interfaces | Ethernet (1000 Base-T / 100 Base-TX / 10 Base-T) |
| Supported protocols | SNMP (version1, 2C, 3), SMI-S 1.6 |
| Administration | Web-based graphical user interface, CLI (Command Line Interface), ETERNUS SF |
| Remote Support | Event notification (E-mail / SNMP / Syslog), Remote maintenance |

Supported configurations

All major host operating systems, servers and business applications
 Detailed support matrix:
www.fujitsu.com/global/support/products/computing/storage/disk/supported-configurations

Installation specification

| | |
|---------------------------|---|
| 19" rackmount | Yes |
| Service Area | Front: 850 mm (33.5 inch) or more Rear: 850 mm (33.5 inch) or more |
| Power voltage | AC 100 - 120 V / AC 200 - 240 V |
| Power frequency | 50 / 60 Hz |
| Power supply efficiency | 92 % (80 PLUS gold) |
| Maximum Power Consumption | AC 100 - 120 V: 26,240 W (26,800 VA) |
| Maximum Power Consumption | AC 200 - 240 V: 26,520 W (27,080 VA) |
| Power phase | Single |

| | ETERNUS DX600 S3 | 2.5-inch Drive Enclosure | 3.5-inch Drive Enclosure | High-Density Drive Enclosure |
|--|---|--|--|---|
| Dimensions (W x D x H) | 482 x 805 x 133 mm 19 x 31.7 x 5.2 inch 3 U | 482 x 540 x 88 mm 19 x 21.3 x 3.5 inch 2 U | 482 x 560 x 88 mm 19 x 22 x 3.5 inch 2 U | 482 x 980 x 176 mm 19 x 38.6 x 6.9 inch 4 U |
| Weight | 54 kg (119 lb) | 35 kg (77 lb) | 35 kg (77 lb) | 95 kg (209 lb) |
| Maximum Power Consumption (AC 100 - 120 V) | 720 W (730 VA) | 430 W (440 VA) | 340 W (350 VA) | 1,300 W (1,320 VA) |
| Maximum Power Consumption (AC 200 - 240 V) | 1,000 W (1,010 VA) | 430 W (440 VA) | 340 W (350 VA) | 1,300 W (1,320 VA) |

Environment

| | |
|-----------------------------|--|
| Maximum Heat Generation | AC 100 - 120 V: 97,200: kJ/h AC 200 - 240 V: 98,200: kJ/h |
| Temperature (operating) | 10 - 40 °C |
| Temperature (not operating) | 0 - 50 °C |

Environment

| | | | | |
|-------------------------------|---|--------------------------|--------------------------|------------------------------|
| Humidity (operating) | 20 - 80 % (relative humidity, non-condensing) | | | |
| Humidity (not operating) | 8 - 80 % (relative humidity, non-condensing) | | | |
| Altitude | 3,000 m (10,000 ft.) | | | |
| Sound pressure (LpAm) | 54dB(A) | | | |
| Sound power (LWAd; 1B = 10dB) | 7.2B | | | |
| Noise notes | Measured with single enclosure according to ISO 7779 and declared according to ISO 9296 | | | |
| Operating environment | FTS 04230 – Guideline for Data Center (installation specification) | | | |
| Operating environment link | http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe | | | |
| Type | ETERNUS DX600 S3 | 2.5-inch Drive Enclosure | 3.5-inch Drive Enclosure | High-Density Drive Enclosure |

Compliance

| | | | | |
|-------------------------------|---|--|--|--|
| Product safety | UL 60950-1, CSA-C22.2 No. 60950-1, EN 60950-1, IEC 60950-1, GOST-R | | | |
| Electromagnetic Compatibility | CNS 13438, FCC CFR 47 class A , ICES 003 Class A, EN 55022 Class A, VCCI Class A, AS/NZS CISPR 22 Class A | | | |
| Electromagnetic Immunity | EN 55024 | | | |
| CE certification | 2004/108/EC, 2006/95/EC, 2011/65/EC | | | |
| Approvals | CB, CE, C-Tick, FCC, EAC, GS, VCCI | | | |
| Environmental compliance | RoHS compliant, WEEE compliant | | | |
| Compliance notes | There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. | | | |
| Compliance link | http://globalsp.ts.fujitsu.com/sites/certificates | | | |

Warranty

| | | | | |
|-----------------------------|--|--|--|--|
| Warranty period | 3 years | | | |
| Warranty type | Onsite warranty | | | |
| Warranty Terms & Conditions | www.fujitsu.com/support | | | |

Product Support Services - the perfect extension

| | | | | |
|----------------------|--|--|--|--|
| Support Pack Options | Available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time | | | |
| Recommended Service | 24x7, Onsite Response Time: 4h | | | |
| Service Lifecycle | 5 years after end of product life | | | |
| Service Weblink | www.fujitsu.com/services/product-services | | | |

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ETERNUS DX600 S3, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ETERNUS DX600 S3, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/eternus

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

© Copyright 2016 Fujitsu Limited. Fujitsu, the Fujitsu logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners.

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Limited
 Website: www.fujitsu.com/eternus
 2016-09-01 WW-EN



www.forefrontec.com
info@forefrontec.com

Jebel Ali Free Zone, Dubai(HO)
 Street No. N503 - FD03, FD04 & FD05
 United Arab Emirates
 P.O. Box 17020

Tel: +971 (4) 881 44 40
 Fax: +971 (4) 881 42 42

Al Olaya Street, Riyadh(BO)
 Akariyah-3 Building, Office 610
 Kingdom of Saudi Arabia
 P.O. Box 301807, Riyadh 11372

Tel: +966 (11) 460 35 80
 Fax: +966 (11) 460 35 85

Qasim Zainah Street, Jeddah(BO)
 Al-Rawdah, Al-Rawdah Plaza,
 Office 204
 Kingdom of Saudi Arabia

Tel: +966 (12) 612 14 63
 Fax: +966 (12) 612 05 17

Forefront Technologies(BO)
 Musheireb - Palestine St.,
 Doha - Qatar

Tel: +974 (3) 394 47 59
 Fax: +971 (4) 881 42 42

Forefront Technologies(BO)
 Khuwair,
 Muscat, Oman

Tel: +968 (9) 774 24 70
 Fax: +971 (4) 881 42 42